



| RESUMO AÇO CA-50 |          |                |               |
|------------------|----------|----------------|---------------|
| ø(mm)            | COMP.(m) | PESO<br>(Kg/m) | TOTAL<br>(Kg) |
| 6.3              | 35.6     | .250           | 8.9           |
| 8                | 50.5     | .4             | 20.2          |
| 10               | 49.7     | .630           | 31.1          |
| TOTAL            |          |                | 60.2          |

| RESUMO AÇO CA-50 |          |             |            |
|------------------|----------|-------------|------------|
| ø(mm)            | COMP.(m) | PESO (Kg/m) | TOTAL (Kg) |
| 6.3              | 29.2     | .250        | 7.3        |
| 8                | 53.3     | .4          | 21.3       |
| 10               | 1991.2   | .630        | 1244.5     |
| TOTAL            |          |             | 1273.1     |

SIMBOLOGIA:

| RAIOS (r) INTERNOS MÍNIMOS DE CURVATURA<br>PARA GANCHOS E ESTRIBOS NBR-6118<br>(ITEM 6.3.4.1) |       |       |
|-----------------------------------------------------------------------------------------------|-------|-------|
| BITOLA Ø                                                                                      | CA-50 | CA-60 |
| < 20mm                                                                                        | 2.5 Ø | 3.0 Ø |
| > 20mm                                                                                        | 4.0 Ø | 5.0 Ø |
| ESTRIBO<br>> 20mm                                                                             | 1.5 Ø | 1.5 Ø |



SEM ESC.

ev > 2cm  
0.5 Ø MAX. AGREG.

eh > 2cm  
1.2 Ø MAX. AGREG.

4